



Image shown may not reflect actual package.

PRIME

**1825 e kW 2281 kVA
60 Hz 1800 rpm 480 Volts**

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

EMISSIONS / FUEL STRATEGY

- Low Emissions

UL 2200

- UL 2200 Listed configuration available

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Caterpillar® dealers provide extensive post sale support including maintenance and repair agreements
- Caterpillar dealers fill 99.7% of parts orders within 24 hours
- Caterpillar dealers have over 1,798 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

CAT 3516B TA DIESEL ENGINE

- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke-cycle diesel engine combines consistent performance and excellent fuel economy with minimum weight

CAT SR4B GENERATOR

- Matched to the performance and output characteristics of Caterpillar engines
- Optimum winding pitch for minimum total harmonic distortion and maximum efficiency
- Single point access to accessory connections
- UL 1446 recognized Class H insulation

CAT EMCP3 CONTROL PANELS

- Controls designed to meet individual customer needs:
- EMCP 3 provides the option for full-featured power metering and protective relaying
- Segregated low voltage, AC/DC accessory box provides single point access to accessory connections



4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

GeneratorJoe



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Single element canister type air cleaner • Service indicator 	<ul style="list-style-type: none"> • Dual element & heavy duty air cleaners (with pre-cleaners) • Air inlet adapters & shutoff
Cooling	<ul style="list-style-type: none"> • Radiator with guard (43°C) • Low Profile with (frontal area) • Low airflow • Radiator duct flange • Coolant drain line with valve • Fan and belt guards • Caterpillar Extended Life Coolant* • Coolant level sensors *Not included with packages without radiators 	<ul style="list-style-type: none"> • Radiator with 27°C and 50°C ambient capability • Radiator option for 57°C ambient with treated water • Radiator removal • Heavy duty, harsh environment radiator at 43°C and 50°C • Heat exchanger and expansion tank • Coolant level switch gauge • Jacket water heater
Exhaust	<ul style="list-style-type: none"> • Dry exhaust manifold • Flanged faced outlets 	<ul style="list-style-type: none"> • Mufflers and Silencers • Stainless steel exhaust flex fittings • Elbows, flanges, expanders & Y adapters
Fuel	<ul style="list-style-type: none"> • Secondary fuel filters • Fuel priming pump • Flexible fuel lines • Fuel cooler* *Not included with packages without radiators 	<ul style="list-style-type: none"> • Water separator • Duplex fuel filter
Generator	<ul style="list-style-type: none"> • Permanent magnet excited • Class H insulation • Class F temperature (105°C prime/130°C standby) • Winding temperature detectors(select models) • Anti-condensation space heaters 	<ul style="list-style-type: none"> • Oversize & premium generators
Power Termination	<ul style="list-style-type: none"> • Bus bar (NEMA and IEC meachanicallug holes) -right side standard • Top and bottom cable entry 	<ul style="list-style-type: none"> • Circuit breakers, UL listed, 3 pole with shunt trip, 80% or 100% rated, choice of trip units, manual or electrically operated (low voltage only) • Circuit breakers, IEC compliant, 3 or 4 pole with shunt trip (low voltage only), choice of trip units, manual or electrically operated • Shroud cover for bottom cable entry • Power terminations can be located on the left and/or rear as an option. Also, multiple circuit breakers can be ordered (up to 3)
Governor	<ul style="list-style-type: none"> • ADEM™ 3 	<ul style="list-style-type: none"> • Load share module
Control Panels	<ul style="list-style-type: none"> • User Interface panel (UIP) - rear mount • EMCP3.1 Genset Controller • Voltage and Speed adjust • AC&DC customer wiring area (right side) • CAT digital voltage regulator (CDVR) with KVAR/PF control, 3-phase sensing • Reactive droop • Emergency Stop Pushbutton 	<ul style="list-style-type: none"> • EMCP3.3 • Option for right or left mount UIP • Local & remote annunicator modules • Load share module • Discrete I/O module • Generator temperature monitoring & protection
Lube	<ul style="list-style-type: none"> • Lubricating oil and filter • Oil drain line with valves • Fumes disposal • Gear type lube oil pump 	<ul style="list-style-type: none"> • Oil level regulator • Deep sump oil pan • Electric & air prelube pumps • Manual prelube with sump pump • Duplex oil filter
Mounting	<ul style="list-style-type: none"> • Structural steel tube • Anti-vibration mounts (shipped loose) 	<ul style="list-style-type: none"> • Isolator removal Spring-type isolator, zone 4
Starting/Charging	<ul style="list-style-type: none"> • 24 volt starting motor(s) • Batteries with rack and cables • Battery disconnect switch 	<ul style="list-style-type: none"> • Battery chargers (10&20AMP) •45 amp charging alternator • Oversize batteries • Ether starting aid • Heavy duty starting motors • Barring device (manual) • Air starting motor with control & silencer

SPECIFICATIONS

 **CAT GENERATOR**

SR4B Generator
 Frame size..... 825
 Excitation..... Permanent Magnet
 Pitch..... 0.6667
 Number of poles..... 4
 Number of bearings..... Single Bearing
 Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion
 IP rating..... Drip Proof IP22
 Alignment..... Pilot Shaft
 Overspeed capability - % of rated..... 150
 Wave form..... 003.00
 Paralleling kit/Droop transformer..... Standard
 Voltage regulator.3 Phase sensing with selectible volts/Hz
 Voltage regulation..... Less than +/- 1/2% (steady state)
 Less than +/- 1% (no load to full load)
 Telephone Influence Factor..... Less than 50
 Harmonic Distortion..... Less than 5%

 **CAT DIESEL ENGINE**

3516B TA, V-16, 4-stroke-cycle watercooled diesel
 Bore - mm..... 170.00 mm (6.69 in)
 Stroke - mm..... 190.00 mm (7.48 in)
 Displacement - L..... 69.00 L (4210.64 in³)
 Compression ratio..... 14.0:1
 Aspiration..... TA
 Fuel system..... Electronic unit injection

 **CAT EMCP3 CONTROL PANELS**

- EMCP 3.1 (standard)
- EMCP3.3 (additional features)
- Integral to generator terminal box
- Single location for customer connection
- 24 Volt DC Control
- IP 23 enclosure
- Electronically dead front
- Lockable hinged door (option)
- UL/CSA/CE
- Generator terminal box mounted
- Panel illuminating lights
- Auto start/stop control
- Voltage adjust (optional on 3.1)
- True RMS metering, 3-phase
- Digital indications for:
 - RPM
 - Operating hours
 - Oil pressure
 - Coolant temperature
 - System DC volts
- Shutdowns with indicating lights for:
 - Low oil pressure
 - High coolant temperature
 - Overspeed
 - Emergency stop
 - Failure to start (overcrank)
- Programmable protective relaying functions:
 - Under and over voltage
 - Under and over frequency
 - Reverse power
- Overcurrent
- MODBUS isolated data link (RS-485 half-duplex) supports 3.3 serial communication at data rate up to 115.2 kbaud (*)



4016 Quartz Drive
 Santa Rosa, CA 95405
 Phone: 707 539-9003
 Fax: 707 539-5212
 Email: sales@generatorjoe.NET
 Web www.generatorjoe.NET

GeneratorJoe

TECHNICAL DATA

Open Generator Set - - 1800 rpm/60 Hz/480 Volts	DM7930	
Package Performance Genset Power rating with fan Genset Power rating @ 0.8 pf	1825 ekW 2281.25 kVA	
Low Emissions Coolant to aftercooler temp max	90 ° C	194 ° F
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	496.6 L/hr 373.6 L/hr 260.1 L/hr	131.2 Gal/hr 98.7 Gal/hr 68.7 Gal/hr
Cooling System¹ Ambient air temperature Air flow (max @ rated speed for radiator arrangement) Engine coolant capacity Radiator coolant capacity Engine Coolant capacity with radiator/exp. tank	42 ° C 1841 m ³ /min 233.0 L 18.8 L 251.8 L	108 ° F 65014 cfm 61.6 gal 5.0 gal 66.5 gal
Inlet Air Combustion air inlet flow rate	161.6 m ³ /min	5706.9 cfm
Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	498.9 ° C 436.7 m ³ /min 203.2 mm 6.7 kPa	930.0 ° F 15421.9 cfm 8.0 in 26.9 in. water
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to aftercooler Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	779 kW 1973 kW 392 kW 155 kW 68.2 kW	44302 Btu/min 112204 Btu/min 22293 Btu/min 8815 Btu/min 3878.5 Btu/min
Alternator² Motor starting capability @ 30% voltage dip Frame Temperature Rise	4647 skVA 825 105 ° C	221 ° F
Lube System Sump refill with filter	401.3 L	106.0 gal
Emissions (Nominal)³ NOx g/hp-hr CO g/hp-hr HC g/hp-hr PM g/hp-hr	6.88 g/hp-hr .37 g/hp-hr .14 g/hp-hr .09 g/hp-hr	

¹ Ambient capability at 300 m (984ft) above sea level. For ambient capability at other altitudes, consult your Caterpillar dealer.

² UL 2200 Listed packages may have oversized generators with a different temperature rise and motor starting characteristics. Generator temperature rise is based on a 40 degree C ambient per NEMA MG1-32.

³ Emissions data measurements are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. This engine's exhaust emissions are in compliance with the US EPA and California nonroad regulations as identified above. Data shown is based on steady state operating conditions of 77° F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations.



4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

GeneratorJoe

PRIME 1825 kW 2281 kVA

60 Hz 1800 rpm 480 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: -ABGSM TM3, AS1359, AS2789, BS4999, BS5000, BS5514, DIN6271, DIN6280, EGSA101P, IEC34/1, ISO3046/1, ISO8528, JEM1359, NEMA MG 1-22, VDE0530, 89/392/EEC, 89/336/EEC

Prime - Output available with varying load for an unlimited time. Prime power in accordance with ISO8528. 10% overload power in accordance with ISO3046/1, AS2789, DIN6271, and BS5514 available on request. Prime power ambients shown indicate ambient at 100 percent load which results in a coolant top tank temperature just below the alarm temperature.

Ratings are based on SAE J1995 standard conditions. These ratings also apply at ISO3046/1, DIN6271, and BS5514 standard conditions.

Fuel Rates are based on fuel oil of 35° API (16° C or 60° F) gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.).

Additional Ratings may be available for specific customer requirements. Consult your Caterpillar representative for details.



4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

GeneratorJoe

PRIME 1825 ekW 2281 kVA

60 Hz 1800 rpm 480 Volts



DIMENSIONS

Package Dimensions		
Length	6075.2 mm	239.18 in
Width	2587.6 mm	101.87 in
Height	3015.1 mm	118.7 in
Weight	16 293 kg	35,920 lb

Note: Do not use for installation design.
See general dimension drawings for detail (Drawing #2748723).



4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

GeneratorJoe

Performance No.: DM7930

Feature Code:: 516DE3R

Source:: U.S. Sourced

25 January 2006

6068592

© 2006 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos and "Caterpillar Yellow," as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.