



Image shown may not reflect actual package.

STANDBY

550 kW 687 kVA

60 Hz 1800 rpm 480 Volts

Caterpillar is leading the power generation marketplace with Power Solutions engineered to deliver unmatched flexibility, expandability, reliability, and cost-effectiveness.

FEATURES

FUEL/EMISSIONS STRATEGY

- Tier 2 and Low Emissions

RATING

- Rated for Emergency Standby Power (ESP) per ISO8528
- 200 Hours / year operation

FULL RANGE OF ATTACHMENTS

- Wide range of bolt-on system expansion attachments, factory designed and tested

SINGLE-SOURCE SUPPLIER

- Fully prototype tested with certified torsional vibration analysis available

WORLDWIDE PRODUCT SUPPORT

- Caterpillar® dealers provide extensive post sale support including maintenance and repair agreements
- Caterpillar dealers fill 99.7% of parts orders within 24 hours
- Caterpillar dealers have over 1,798 dealer branch stores operating in 200 countries
- The Cat® S•O•SSM program cost effectively detects internal engine component condition, even the presence of unwanted fluids and combustion by-products

UL 2200

- UL 2200 listed packages are available. Certain restrictions may apply. Consult with your Caterpillar dealer network

CAT® C15 ATAAC DIESEL ENGINE

- Utilizes ACERT™ Technology
- Reliable, rugged, durable design
- Field-proven in thousands of applications worldwide
- Four-stroke diesel engine combines consistent performance and excellent fuel economy with minimum weight
- Electronic engine control

CAT GENERATOR

- Designed to match performance and output characteristics of Caterpillar diesel engines
- 2/3 Pitch
- UL 1446 Recognized Class H Insulation

CAT EMCP 3 CONTROL PANELS

- Controls designed to meet individual customer needs
- Options for power metering and protective relaying are available
- Options to meet UL/CSA/NFPA
- Rear mounted power center provides convenient location for control panel, and optional circuit breakers



GeneratorJoe

4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET



FACTORY INSTALLED STANDARD & OPTIONAL EQUIPMENT

System	Standard	Optional
Air Inlet	<ul style="list-style-type: none"> • Light Duty Air filter 	<ul style="list-style-type: none"> • Canister Style Air Cleaners • Air Cleaner - single stage • Dual element • Heavy duty
Cooling	<ul style="list-style-type: none"> • Radiator package mounted(50°C) • Coolant drain line with valve terminated at edge of base • Fan and belt guards • Coolant level sight gauge • Caterpillar Extended Life Coolant 	<ul style="list-style-type: none"> • Radiator removal • Radiator duct flange & guard
Exhaust	<ul style="list-style-type: none"> • Dry exhaust manifold • Flanged faced outlets • Stainless Steel Flex with split-cuff connection 	<ul style="list-style-type: none"> • Mufflers • Manifold & Turbocharger guards • Elbows
Fuel	<ul style="list-style-type: none"> • Primary fuel filter with integral water separator • Secondary fuel filters • Fuel priming pump • Engine fuel transfer pump • Flex fuel lines • Engine fuel transfer pump • Fuel cooler* *Not included with packages without radiators 	<ul style="list-style-type: none"> • Integral UL listed fuel tank base • Manual transfer pump • Fuel level switch
Generator	<ul style="list-style-type: none"> • Self excited • Class H insulation • Random Wound • 2/3 pitch • R448 voltage regulator with load adjustment module • IP23 Protection 	<ul style="list-style-type: none"> • Permanent magnet excitation • CDVR with KVAR/PF control • AREP Excitation • Oversize and premium generators • Bearing/Stator temperature detection (premium generator) • 3 phase sensing • Anti-condensation space heaters • Cable access box • Reactive droop
Power Termination	<ul style="list-style-type: none"> • Power Terminator Strips Mounted inside Power Center • Segregated low voltage wiring panel 	<ul style="list-style-type: none"> • Circuit breakers, UL listed, 3 pole • Circuit breakers, IEC compliant, 3 pole • Circuit breaker Shunt trip • Circuit breaker Auxillary contact • Top & bottom power cable entry • Floor standing UL breakers
Governor	<ul style="list-style-type: none"> • ADEM™A4 	<ul style="list-style-type: none"> • Load share module
Control Panels	<ul style="list-style-type: none"> • EMCP 3.1 (rear mounted) • Speed adjust • Emergency stop pushbutton • Voltage adjust 	<ul style="list-style-type: none"> • EMCP 3.2 & EMCP 3.3 (can be RH mounted) • Local annunciator modules (NFPA 99/110) • Remote annunciator modules (NFPA 99/110) • Discrete I/O module
Lube	<ul style="list-style-type: none"> • Lubricating oil and filter • Oil drain line with valves • Fumes disposal • Gear type lube oil pump 	<ul style="list-style-type: none"> • Manual sump pump
Mounting	<ul style="list-style-type: none"> • Formed steel wide base frame • Linear vibration isolation-seismic zone 4 	<ul style="list-style-type: none"> • Formed steel wide base frame
Starting/Charging	<ul style="list-style-type: none"> • 24 volt starting motor • 45 amp charging alternator • Battery with rack and cables 	<ul style="list-style-type: none"> • Jacket water heater with shut off valves • Block heater • Ether starting aids • Battery disconnect switch • Battery charger(5A,10A) • Oversize batteries
General	<ul style="list-style-type: none"> • Paint - Caterpillar yellow except rails and radiators gloss black • Flywheel and flywheel housing - SAE No.1 	

SPECIFICATIONS

CAT GENERATOR

Frame size..... LC6114G
Excitation..... Self Excited
Pitch..... 0.6667
Number of poles..... 4
Number of bearings..... Single Bearing
Insulation..... UL 1446 Recognized Class H with tropicalization and antiabrasion
- Consult your Caterpillar dealer for available voltages
IP Rating..... Drip Proof IP22
Alignment..... Pilot Shaft
Overspeed capability..... 125% of rated
Wave form Deviation (Line to Line)..... 2%
Voltage regulator.3 Phase sensing with selectable volts/Hz
Voltage regulation..... Less than +/- 1/2% (steady state)
Less than +/- 1/2% (w/ 3% speed change)
Telephone influence factor..... Less than 50
Harmonic Distortion..... Less than 5%

CAT DIESEL ENGINE

C15 ATTAC, L-6, 4-stroke water-cooled diesel
Bore..... 137.20 mm (5.4 in)
Stroke..... 171.40 mm (6.75 in)
Displacement..... 15.20 L (927.56 in³)
Compression Ratio..... 16.1:1
Aspiration..... ATAAC
Fuel System..... MEUI
Governor Type..... Caterpillar ADEM control system

CAT EMCP 3 CONTROL PANELS

- EMCP 3.1 (Standard)
- UL/CSA/CE
- NEMA 1, IP22 enclosure
- Run/Auto/Stop control
- True RMS metering, 3-phase
- Speed Adjust
- Vandal cover (option)
- Voltage adjust
- Digital Indication for:
 - RPM
 - Operating hours
 - Oil Pressure
 - Coolant temperature
 - System DC volts
 - L-L volts, L-N volts, phase amps, Hz
 - ekW, kVA, kVAR, kW-hr, %kW, PF, (EMCP3.2/3.3)
- Shutdowns with common indicating light for:
 - Low oil pressure
 - High coolant temperature
 - Low coolant level
 - Overspeed
 - Emergency stop
 - Failure to start (overcrank)
- Programmable protective relaying functions: (EMCP 3.2 & 3.3)
 - Under and over voltage
 - Under and over frequency
 - Reverse power
 - Overcurrent
- MODUS isolated data link (RS-485 half-duplex EMCP 3.2 & 3.3)



GeneratorJoe

4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

TECHNICAL DATA

Open Generator Set - - 1800 rpm/60 Hz/480 Volts	DM8157	
Tier 2 and Low Emissions		
Package Performance Genset Power EKW Genset Power rating with fan	550 ekW 550 ekW	
Fuel Consumption 100% load with fan 75% load with fan 50% load with fan	156.8 L/hr 117.6 L/hr 92.8 L/hr	41.4 Gal/hr 31.1 Gal/hr 24.5 Gal/hr
Cooling System¹ Ambient air temperature Air flow restriction (system) Air flow (max @ rated speed for radiator arrangement) Engine Coolant capacity with radiator/exp. tank Engine coolant capacity Radiator coolant capacity	° C 0.12 kPa m ³ /min 20.8 L 20.8 L L	0.48 in. water 5.5 gal 5.5 gal
Inlet Air Combustion air inlet flow rate	44.1 m ³ /min	1557.4 cfm
Exhaust System Exhaust stack gas temperature Exhaust gas flow rate Exhaust flange size (internal diameter) Exhaust system backpressure (maximum allowable)	518.4 ° C 123.8 m ³ /min mm 6.8 kPa	965.1 ° F 4372.0 cfm 27.3 in. water
Heat Rejection Heat rejection to coolant (total) Heat rejection to exhaust (total) Heat rejection to atmosphere from engine Heat rejection to atmosphere from generator	211 kW 557 kW 115 kW 32.6 kW	12000 Btu/min 31677 Btu/min 6540 Btu/min 1854.0 Btu/min
Alternator² Motor starting capability @ 30% voltage dip Frame Temperature Rise	1445 skVA LC6114G 130 ° C	266 ° F
Lube System Sump refill with filter	L	
Emissions (Nominal)³ NOx g/hp-hr CO g/hp-hr HC g/hp-hr PM g/hp-hr	5.14 g/hp-hr .27 g/hp-hr .01 g/hp-hr .018 g/hp-hr	

¹ Ambient capability at 300m (984 ft) above sea level. For ambient capability at other altitudes, consult your Caterpillar dealer. Air flow restriction (system) is added to existing restriction from factory. Generator temperature rise is based on a 40 C (104 F) ambient per NEMA MG1-32

² Generator temperature rise is based on a 40° C (104° F) ambient per NEMA MG1-32.

³ Emissions data measurements are consistent with those described in EPA CFR 40 Part 89, Subpart D & E and ISO8178-1 for measuring HC, CO, PM, NOx. Data shown is based on steady state operating conditions of 77°F, 28.42 in HG and number 2 diesel fuel with 35° API and LHV of 18,390 btu/lb. The nominal emissions data shown is subject to instrumentation, measurement, facility and engine to engine variations.



GeneratorJoe

4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

STANDBY 550 ekW 687 kVA

60 Hz 1800 rpm 480 Volts



RATING DEFINITIONS AND CONDITIONS

Meets or Exceeds International Specifications: AS1359, AS2789, CSA, EGSA101P, IEC60034, ISO3046, ISO8528, NEMA MG 1-32, UL508, 72/23/EEC, 89/336/EEC, 98/37/EEC.

Standby - Output available with varying load for the duration of the interruption of the normal source power. Standby power in accordance with ISO8528. Fuel stop power in accordance with ISO3046, AS2789, and BS5514. Standby ambient temperatures shown indicate a coolant top tank temperature just below shutdown at 100 percent load.

Prime - Output available with varying load for an unlimited time. Prime power in accordance with ISO8528. 10% overload power in accordance with ISO3046, AS2789, and BS5514. Prime ambient temperatures shown indicate a coolant top tank temperature just below shutdown at 100 percent load.

Ratings are based on SAE J1995 standard conditions. These ratings also apply at ISO3046 standard conditions.

Fuel rates are based on fuel oil of 35° API [16° C (60° F)] gravity having an LHV of 42 780 kJ/kg (18,390 Btu/lb) when used at 29° C (85° F) and weighing 838.9 g/liter (7.001 lbs/U.S. gal.). Additional ratings may be available for specific customer requirements. Consult your Caterpillar representative for details.



Generator Joe

4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

STANDBY 550 ekW 687 kVA

60 Hz 1800 rpm 480 Volts



DIMENSIONS

Package Dimensions		
Length	3775.1 mm	148.63 in
Width	1110.0 mm	43.7 in
Height	2091.0 mm	82.32 in
Weight	3930 kg	8,664 lb

Note: Do not use for installation design.
See general dimension drawings for detail (Drawing #2781051).



GeneratorJoe

4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212
Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

Performance No.: DM8157

Feature Code:: C15DE06

Source:: U.S. Sourced

22 February 2006

6069186

© 2006 Caterpillar
All rights reserved.

Materials and specifications are subject to change without notice.
The International System of Units (SI) is used in this publication.

CAT, CATERPILLAR, their respective logos and "Caterpillar Yellow," as well as corporate and product identity used herein, are trademarks of Caterpillar and may not be used without permission.