





GeneratorJoe



Made in the USA!



Commercial Prime Series Model: 180 CP-3

Ratings

Three Phase Only

60 Hz Standby: kW 180.0
kVA 225.0

Natural Gas Only

Features

- Single source responsibility for the generator set and accessories.
- Prototype and production tested to insure one step load acceptance per NFPA 110.
- Two year limited warranty on generator sets and accessories.
- Unit conforms to NEMA, UL, ANSI and other standards.
- Heavy duty 4 cycle industrial engine for reliability and fuel efficiency.
- Brushless rotating field generator with class H insulation.
- Heavy duty steel base with integral vibration isolators.
- Electronic Isochronous Governor.
- EPA .
- Aluminum powder coated housing.
- Deep Sea 7420 controller.
- ABB breakers.
- Extended oil/radiator drains.
- 6 Amp battery charger.

Generator	Voltage	PH	Hz	Natural Gas		Power Lead Connections
				kW/kVA	Amps	
130 PR-3-2	120/208	3	60	180/225	625	12 Lead Low Wye
130 PR-3-3	120/240	3	60	180/225	542	12 Lead High Delta
130 PR-3-4	277/480	3	60	180/225	271	12 Lead High Wye
130 PR-3-5	127/220	3	60	180/225	591	12 Lead Low Wye
130 PR-3-16	346/600	3	60	180/225	217	4 Lead Wye 3 Ph

RATINGS: All three phase gen-sets are 12 lead windings, rated at (.8) power factor. 105°C "PRIME RATINGS" are strictly for gen-sets provide the prime source of electric power, where normal utility power is unavailable or unreliable. A 10% overload is allowed for a total of 1 hour, within every 12 hours of operation of PRIME RATED systems. All gen-set power ratings are based on temperature rise measured by resistance method as defined by MIL-STD 705C and IEEE STD 115, METHOD 6.4.4. All generators have class H (180°C) insulation system on both rotor and stator windings. All factory tests and KW/KVA charts shown above are based on 105°C (prime) R/R winding temperature, within a maximum 40°C ambient condition. Specifications & ratings are subject to change without prior notice.

ENGINE

Manufacturer Power Solutions (PSI)
Model and Type..... Heavy Duty , 11.1LTCAC, 4 cycle
Aspiration..... Turbocharged & Charge Air Cooled
Cylinder Arrangement 6 Cylinders, Inline
Displacement Cu. In. (Liters)..... 674 (11.1)
Bore & Stroke In. (Cm.)..... 4.84 x 6.1 (12.3 x 15.5)
Compression Ratio 10.5:1
Main Bearings & Style 7, Precision Half-Shell
Cylinder Head..... Cast Iron
Pistons Cast Aluminum
Crankshaft Forged Steel
Exhaust Valve..... inconel, A193
Governor..... Electronic
Frequency Reg. (no load-full load)..... Isochronous
Frequency Reg. (steady state)..... ± 1/4%
Air Cleaner..... Dry, Replaceable Cartridge
Engine Speed.....1800 rpm
Piston Speed, ft/min (m./min)1831 (558)
Max Power, bhp (kwm) Prime/NG.....272 (203)
Ltd. Warranty Period . 12 Months or 2000 hrs., first to occur

FUEL SYSTEM

Type..... NAT. GAS, Vapor Withdrawal
Fuel Pressure (kpa), in. H₂O* (1.74), 7"
Secondary Fuel Regulator.....NG Vapor System
Auto Fuel Lock-Off Solenoid Standard on all sets
Fuel Supply Inlet Line 2" NPTF
* Measured at gen-set fuel inlet, downstream of any dry fuel accessories.

FUEL CONSUMPTION

NAT. GAS: FT ³ /HR (M ³ /HR)	PRIME
100% LOAD	1980 (56.1)
75% LOAD	1500 (42.5)
50% LOAD	1075 (30.4)

NG = 1000 BTU X FT³ = Total BTU/HR

OIL SYSTEM

Type..... Full Pressure
Oil Pan Capacity qt. (L) 26.4 (25.0)
Oil Pan Cap. W/ filter qt. (L) 28.8 (27.0)
Oil Filter 1, Replaceable Spin-On

ELECTRICAL SYSTEM

Ignition SystemElectronic
Eng. Alternator/Starter: ... 24 VDC, negative ground, 45 amp/hr.
Recommended battery to -18°C (0° F): ...(2) 12 VDC, BC# 27,
Max. Dimensions: 12"lg x 6 3/4" wi x 9" hi, with standard
round posts. Min output 700 CCA. Battery tray (max. dim.
at 12"lg x 7"wi). This model has (2) battery trays, (2) hold
down straps, (2) sets of battery cables, and (1) battery
charger. Installation of (2) 12VDC starting batteries con-
nected in series for 24VDC output is required, with possi-
ble higher AMP/HR rating, as described above, if the nor-
mal environment temperature averages -13° F (-25°C) or
cooler.

COOLING SYSTEM

Type of System Pressurized, closed recovery
Coolant PumpPre-lubricated, self-sealing
Cooling Fan Type (no. of blades)Pusher (12)
Fan Diameter inches (cm)38" (965)
Ambient Capacity of Radiator °F (°C)..... 125 (51.6)
Engine Jacket Coolant Capacity Gal (L).....5.5 (21.0)
Radiator Coolant Capacity (Gal.(L).....30.6 (116)
Maximum Restriction of Cooling Air Intake
and discharge side of radiator in. H₂O (kpa) 0.5 (.125)
Water Pump Capacity gpm (L/min).....75 (284)
Heat Reject Coolant : Btu/min (kw).....8100(142)
Low Radiator Coolant Level Shutdown.....Standard
Note: Coolant temp. shut-down switch setting at 230°F (110°C) with 50/50
(water/antifreeze) mix.

COOLING AIR REQUIREMENTS

Combustion Air, cfm (m³/min).....448 (12.7)
Radiator Air Flow cfm (m³/min)..... 18,000 (510)
Heat Rejected to Ambient:
Engine: kw (btu/min).....60.3 (3430)
Alternator: kw (btu/min).....16 (910)

EXHAUST SYSTEM

Exhaust Outlet Size 5"
Max. Back Pressure in. hg (KPA)3.0 (10.2)
Exhaust Flow, at rated kw: cfm (m³/min) 1425 (40.3)
Exhaust Temp., at rated kw: °F (°C)..... 1382 (750)
Engines are EPA certified for Natural Gas.



GeneratorJoe

Email: sales@generatorjoe.Net
Web: www.generatorjoe.NET

ALTERNATOR SPECIFICATIONS

STANDARDS: Marathon MagnaPlus and MagnaMax generators meet UL Listed Electric Generator, American and other international standards such as: NEMA MG1-22, BS5000, CAS C22.2, IEC 34-1 AND VDE 0530. Other standards and certifications can be considered upon request. (Both MagnaPlus & MagnaMax series are built with NEMA Class H Insulation materials or better which are normally rated at 190C degrees total temperature by NEMA however UL laboratories demands the total temperature be derated to a maximum of 160C total temperature when "UL LISTED").

VOLTAGE REGULATOR: SE350, supplied with standard MagnaPlus units and excitation system have solid state voltage build-up, encapsulated for humidity and abrasion protection, 1% regulation, volts per hertz operation, over excitation shutdown, stability adjust and built-in voltage adjustment.

PM300 (optional on MagnaPlus) Supplied with optional PMG excitation support have solid state voltage build-up, encapsulated for humidity and abrasion protection, 1% regulation, volts per hertz operation, over excitation shutdown, stability adjust and built-in voltage adjustment.

DVR2000E+ (optional for MagnaPlus) Standard on MagnaMax voltage regulator and PMG excitation support system are digital, microprocessor design with solid state voltage build-up, encapsulated for humidity and abrasion protection, 1/4% regulation, true volts per hertz operation with adjustable cut in, loss of sensing continuity shutdown, over excitation shutdown, 3 phase RMS sensing, over voltage

protection, and provisions for parallel operation.

PMG Excitation Support System (Standard on MagnaMax) Optional for MagnaPlus, permanent magnet generator excitation support system, minimum short circuit support current of 300% of the rating (250% for 50 hertz) for 10 seconds.

INSULATION SYSTEM: Meet UL1446, UL2200 requirements. Class H materials or better.

MAIN ROTOR: MagnaPlus main rotating field construction shall consist of one piece, four pole laminations, incorporate amortisseur windings to facilitate parallel operation and application to voltage distorting loads. In addition, the amortisseur winding and field pole coil supports may be integrally die cast with the rotor laminations to form a unitized rotor core. The rotating assembly shall be dynamically balanced to less than 2 mils-peak-to-peak-displacement, and shall be designed to have an over speed withstand of 125% of rated speed for 15 minutes when operating at stable rated operating temperature.

VERIFICATION OF PERFORMANCE: (MagnaPlus series) All certified performance and temperature rise test data submitted by generator manufacturer are to be the result of the actual test of the same or duplicate generators. Temperature rise data shall be the result of loaded, rated power factor heat runs at the rated voltage and hertz. All performance testing shall be done in accordance with MIL-STD-705 and/or IEEE Standard-115. Generators are manufactured using production procedures & quality assurance to ISO9001:2008.

DEEP SEA 7420 DIGITAL MICROPROCESSOR CONTROLLER



The 7420 controller is an auto start mains (utility) failure module for single gen-set applications. This controller includes a backlit LCD display which continuously displays the status of the engine and generator at all times.

The 7420 controller will also monitor speed, frequency, voltage, current, oil pressure, coolant temp., and fuel levels. These modules have been designed to display warning and shut down status. It also includes: (11) configurable inputs alerts • (8) configurable outputs alerts • voltage monitoring • mains (utility) failure detection • (250) event logs • configurable timers • automatic shutdown or warning during fault detection • remote start (on load) • engine preheat • advanced metering capability • hour meter • text LCD displays • protected solid state outputs • test buttons for: stop/reset • manual mode • auto mode • lamp test • start button • power monitoring (kWh, kVAh, kVAh)

This controller includes the 7420 expansion features including RS232, RS484 (using MODBUS-RTU/TCP), direct USB connection with PC, expansion optioned using DSE-Net for remote annunciation and remote relay interfacing for a distance of up to 3300FT. The controller software is freely downloadable from the internet and allows monitoring with direct USB cable, LAN, or by internet via the built in web interface.



Further expansion is available by adding the optional "WebNet" gateway interface module. This device will allow comprehensive monitoring of the generator via the cloud including identification, location, and status. Some advantages of this module include: reduced site visits and maintenance costs • remote fuel management • fault analysis • asset tracking • automatic system alerts • maximized system up-time.

GeneratorJoe



GeneratorJoe®
4723 Muirfield Court
Santa Rosa, CA 95405
Phone: 707 542-2224
Fax: 707 542-2227
Email: sales@generatorjoe.net
Web: www.generatorjoe.net

Standard Features and Optional Accessories

Standard Features


- **Heavy duty steel base**
- **Vibration isolators**
- **Oil/radiator drain valve with extension**
- **Battery charger**
- **Battery cables/rack**
- **Circuit breaker**
- **Owners manual**
- **Electronic Isochronous Governor**

Weights and Dimensions

Overall Size, L x W x H, in.: 152 in. x 72 in. x 80 in.

Weight (Wet): 6,475 lbs.

Note: Dim and weights reflect standard open unit with no options



Note: This drawing is provided for reference only and should not be used for planning installation. Contact your local distributor for more detailed information.

Optional Accessories

- PMG
- PMG with DVR regulator
- Block heater
- Battery heater
- Battery charger upgrades (10-20 amp)
- E-stop
- Enclosure lights
- Liquid LP withdrawal
- Dual fuel
- WebNet gateway (remote monitoring)
- NFPA 110 compliance package
- 3 phase sensing
- Generator strip heater
- 8 Lamp Annunciator panel
- Weather enclosure with internal muffler
- Hospital grade silencers
- Oil pan heater
- Flexible fuel lines



GeneratorJoe®

**4723 Muirfield Court
Santa Rosa, CA 95405**

Phone: 707 542-2224


Fax: 707 542-2227

Email: sales@generatorjoe.Net

Web: www.generatorjoe.NET

A disabled veteran owned small business.

Cage 1U5V7 - TIN/EIN #943026355 - Duns #054590203



Made in the USA!



CONTRACTOR

GeneratorJoe

**Commercial Prime Series
Model: 180 CP-3**

Copyright 1996-2014 All Rights Reserved