




GeneratorJoe



Made in the USA!



Shown with optional equipment

Centurion "P" Series Model: 600 CP & CP3

Ratings

Single and/or Three Phase Available

		60 Hz	50 Hz
Standby:	kW	600.0	500.0
	kVA	750.0	625.0
Prime:	kW	540.0	450.0
	kVA	675.0	562.5

Features

- Single source responsibility for the generator set and accessories.
- Prototype and production tested to insure one step load acceptance per NFPA 110.
- Two year limited warranty on generator sets and accessories.
- Unit conforms to CSA, NEMA, EGSA, ANSI and other standards.
- Heavy duty 4 cycle industrial engine for reliability and fuel efficiency.
- Brushless rotating field generator with class H insulation.
- Heavy duty steel base with integral vibration isolators.
- Electronic Isochronous Governor.
- Cooling system designed for ambients up to 50°C (122°F)
- EPA Tier 2 Certified Engine.

Generator	Voltage	PH	Hz	Standby Rating		Prime Rating	
				kW/kVA	Amps	kW/kVA	Amps
HCI544F311	277/480	3	60	600/750	902	540/675	677
	139/240	3	60	600/750	1804	540/675	1624
	254/440	3	60	600/750	984	540/675	886
	127/220	3	60	600/750	1768	540/675	1771
	240/416	3	60	600/750	1024	540/675	937
	120/208	3	60	600/750	2049	540/675	1874
	120/240	3	60	600/750	1775	540/675	1624
	219/380	3	60	538/673	1023	500/625	950
	120/240	1	60	295/295	1229	275/275	1146



RATINGS: All three-phase units are rated at 0.8 power factor. All single-phase units are rated at 1.0 power factor.

STANDBY RATINGS: Standby ratings apply to installations served by a reliable utility source. The standby rating is applicable to varying loads for the duration of a power outage. There is no overload capability for this rating. Ratings are in accordance with ISO-3046/1, BS 5514, AS 2789, and DIN 6271.

PRIME POWER RATINGS: Prime power ratings apply to installations where utility power is unavailable or unreliable. At varying load the number of generator set operating hours is unlimited. A 10% overload capacity is available for one hour in twelve. Ratings are in accordance with ISO-8528/1, overload power in accordance with ISO-3046/1, BS5514, AS2789, and DIN 6271. For limited running time and base load ratings consult the factory. The generator set manufacturer reserves the right to change the design or specifications without notice and without any obligation or liability whatsoever.

GENERAL GUIDELINES FOR DERATION: Altitude: Derate 0.5% per 100m (328 ft.) elevation above 1000m (3279 ft.) Temperature: Derate 1.0% per 10°C (18°F) temperature above 40°C (104°F).

Perkins Diesel Engine

Model 2806C-E18TAG3

Basic technical data

Number of cylinders	6
Cylinder arrangement	Vertical in-line
Cycle	Four stroke
Induction system	Turbocharged, air to air charge cooled
Compression ratio	14.5:1
Bore	5.7 in. (145 mm)
Stroke	7.2 in. (183 mm)
Cubic capacity	1,106.4 cu in. (18.13 L)
Direction of rotation	Anti-clockwise when viewed from flywheel
Firing order	1,5,3,6,2,4

Cooling system

Radiator

Face area	2,712.5 in ² (1.75 m ²)
Number of rows and material	2, Aluminum
Matrix density and material	15.0, Aluminum fins per inch
Width of matrix	54.7 in. (1,390 mm)
Height of matrix	49.6 in. (1,260 mm)
Pressure cap setting	10.0 psi (70 kPa)

Charge cooler

Face area	2,515.6 in ² (1.623 m ²)
Number of rows and material	1, Aluminum
Matrix density and material	14, Aluminum fins per inch
Width of matrix	46.5 in. (1,180 mm)
Height of matrix	54.7 in. (1,390 mm)

Fan

diameter	38 in. (965 mm)
Drive ratio	0.8:1
Number of blades	9
Material	Plastic
Type	Pusher

Coolant

Total system capacity	16.1 gal (61.0 L)
Coolant pump drive	Gear
Maximum top tank temperature	217° F (103° C)
Temperature rise across engine (rating dependent)	
Thermostat operation range	190-208° F (88-98 °C)
Recommended coolant:	50% ethylene glycol with a corrosion inhibitor (BS 658 : 1992 or MOD AL39) and 50% clean fresh water.

Designation	Units	Prime	Standby
		60 Hz	
Gross engine power	hp (kWm)	803 (599)	884 (659)
Net engine power	Hp (kWm)	785 (585)	865 (645)
Brake mean effective pressure	psi (kPa)	322 (2219)	354 (2441)
Engine coolant flow (against 4.4 psi (30 kPa) restriction)	gal/sec (L/sec)	1.9 (7.2)	1.9 (7.2)
Combustion air flow (at rated speed)	cfm (m ³ /min)	1730 (49)	1836 (52)
Exhaust gas flow (max.)	cfm (m ³ /min)	4591 (130)	5050 (143)
Exhaust gas temperature at turbo-charger outlet	°F (°C)	955 (513)	1008 (542)
Overall thermal efficiency (net)	%	41.1	40.6

Exhaust system

Maximum back pressure	0.97 psi (6.7 kPa)
Exhaust outlet size	8.0 in. (202 mm)

Fuel system

Type of injection	MEUI
Fuel injection pump	MEUI
Governor type	electronic
Injector Pressure	29,008 psi (200 MPa)

Fuel lift pump

Lift pump type	gear driven
Lift pump delivery @ 1800 rpm	120.7 gal/hr (457 l/hr)
Lift pump delivery pressure	87 psi (600 kPa)
Maximum suction head	3 m
Maximum static pressure head	4 m
Max. fuel inlet temperature	

Fuel Consumption Gal/Hr (L/Hr.)

Speed	Power Rating		
	Standby	75%	50%
60Hz	41.2 (156.0)	37.0 (140.0)	19.0 (72.0)

Lubrication system

Lubricating oil capacity total system	14.7 gal (55.5 L)
Maximum sump capacity	14.1 gal (53.5 L)
Minimum sump capacity	
Maximum engine operating angles	
Front up, front down, right side or left side	7°

Lubricating oil pressure

Oil flow at 1800 rev/min	0.92 gal/sec (3.48 L/sec)
At maximum no-load speed	61 psi (420 kPa)
Oil temperature (continuous operation)	
Oil consumption at full load as a % of fuel consumption	0.1%

Electrical system

Type	24 volt negative earth
Alternator type	
Alternator voltage	24V
Alternator output	70A
Starter motor type	
Starter motor voltage	24V
Starter motor power	12 hp (9 kW)
Number of teeth on flywheel	136
Number of teeth on starter pinion	11
Minimum cranking speed	115 rev/min

Induction system

Maximum air intake restriction	
Clean filter	0.54 psi (3.7 kPa)
dirty filter	0.93 psi (6.4 kPa)
Air filter type	paper element

4016 Quartz Drive

Santa Rosa, CA 95405

Phone: 707 539-9003

Fax: 707 539-5212

Email: sales@generatorjoe.NET

Web www.generatorjoe.NET

GeneratorJoe

Generator Controller Options



Digital Control Panel

The DGC-2020 digital GenSet controller provides integrated engine-GenSet control, protection, and metering. Microprocessor based technology allows for exact measurement, set point adjustment, and timing functions. Front panel 3 position controls and indicators enable quick and simple operation. The panel is also equipped with a emergency stop push button and an Alarm Horn with silence button. A wide temperature-range liquid crystal display (LCD) with backlighting can be viewed under a wide range of ambient light and temperature conditions down to 104° F (40° C).

Features SAE J1939 Engine ECU communications, Multilingual capability, Remote RS-485 communications for Optional RDP-110 Remote Annunciator, Extremely rugged, fully encapsulated design with 4 programmable contact inputs and 10 contact outputs (2 ADC rated). It also features Modbus Communications with RS-485, Battery Backup for Real Time Clock, UL recognized, CSA certified, CE approved, HALT (Highly Accelerated Life Tests) tested, IP 54 Front Panel rating with integrated gasket, and NFPA 110Level 1 Compatible.



Analog End Mount Controller

This Generator control panel has analog instruments to monitor AC voltage, AC frequency, and percent of load. The analog engine instruments monitor oil pressure, water temperature, battery voltage, fuel level, and run time/hour meter. Safety shutdowns provide red LED indication for overspeed, overcrank, low oil pressure, and high coolant temperature. Provide green LED indication of engine running. Control switch is provided for local and remote starting with 3 position run/off/remote switch. There is also an engine mounted emergency by-pass key switch.

AC Alternator Specifications

STANDARDS

Stamford industrial generators meet the requirements of BS EN 60034 and the relevant section of other international standards such as B55000, VDE 0530, NEMA MG1-32, 1EC34, CSA C22.2-100, A51359. Other standards and certifications can be considered on request.

VOLTAGE REGULATORS

MX341 AVR

This sophisticated AVR is incorporated into the Stamford Permanent Magnet Generator (PMG) control system.

The PMG provides power via the AVR to the main exciter, giving a source of constant excitation power independent of generator output. The main exciter output is then fed to the main rotor, through a full wave bridge, protected by a surge suppressor. The AVR has in-built protection against sustained over-excitation, caused by internal or external faults. This de-excites the machine after a minimum of 5 seconds.

An engine relief load acceptance feature can enable full load to be applied to the generator in a single step.

If three-phase sensing is required with the PMG system the MX321 AVR must be used.

We recommend three-phase sensing for applications with greatly unbalanced or highly non-linear loads.

(Optional) MX321 AVR

The most sophisticated of all our AVRs combines all the features of the MX341 with, additionally, three-phase rms sensing, for improved regulation and performance. Over voltage protection is built-in and short circuit current level adjustments is an optional facility.

WINDINGS & ELECTRICAL PERFORMANCE

All generator stators are wound to 2/3 pitch. This eliminates triplen (3rd, 9th, 15th ...) harmonics on the voltage waveform and is found to be the optimum design for trouble-free supply of non-linear loads. The 2/3 pitch design avoids excessive neutral currents sometimes seen with higher winding pitches, when in parallel with the mains. A frilly connected damper winding reduces oscillations during paralleling. This winding, with the 2/3 pitch and carefully selected pole and tooth designs, ensures very low waveform distortion.

SHAFT

The generator rotor is dynamically balanced to better than B56861:Part 1 Grade 2.5 for minimum vibration in operation.

INSULATION/IMPREGNATION

The insulation system is class H.

All wound components are impregnated with materials and processes designed specifically to provide the high build required for static windings and the high mechanical strength required for rotating components.

QUALITY ASSURANCE

Generators are manufactured using production procedures having a quality assurance level to BS EN ISO 9001.

Standard Features and Optional Accessories

Standard Features

- **Heavy duty steel base**
- **Vibration isolators**
- **Oil drain valve with extension**
- **Battery rack**
- **Battery cables**
- **Water jacket heater**
- **Owners manual**
- **Electronic Isochronous Governor**


Optional Accessories

- Critical Exhaust Silencer
- Flex Exhaust Connector
- End Mount Analog Control Panel
- DGC2020 Digital Control Panel
- Modem for DGC2020
- Enhanced Gen Protection for DGC2020
- Surface Mount Remote Annunciator Panel for DGC2020
- Flush Mount Remote Annunciator Panel for DGC2020
- Remote Mount Break Glass E-Stop Switch
- Line Circuit Breaker
- 3 phase sensing
- Generator strip heater
- Radiator duct flange for open unit
- Weather Enclosure with external muffler
- Weather Enclosure with internal muffler
- Sound Attenuated weather enclosure
- Oil Pan Heater
- Battery
- Battery Charger
- Battery Heaters
- Sub-Base Fuel Tank
- Flexible Fuel Lines

Weights and Dimensions

Overall Size, L x W x H, in.: 144 in. x 72 in. x 84 in.
Weight (Wet): 9,992 lbs.

Note: Dim and weights reflect standard open unit with no options



Note: This drawing is provided for reference only and should not be used for planning installation. Contact your local distributor for more detailed information.



GeneratorJoe

4016 Quartz Drive
Santa Rosa, CA 95405
Phone: 707 539-9003
Fax: 707 539-5212

Email: sales@generatorjoe.NET
Web www.generatorjoe.NET

A small business owned by service a connected disabled veteran.

Cage 1U5V7 - TIN/EIN #943026355 - Duns #054590203



Made in the USA!



Model: 600 CP & CP3