

Features

Honda GX340 Engine

You expect the best; you get the best. The Honda GX340 engine has more power, lower fuel consumption, and lower emissions than previous versions.

Bi-Fuel

Designed to easily run and transition between two fuel sources; natural gas and gasoline.

Low Oil Protection

In the event there is low oil level, the engine will shut down, to protect the engine from damage.

Sturdy Wrap-Around Welded Tubular Cradle

We use 1"-14 gauge steel for dependable durability.

7 Gallon Fuel Tank

The EPA-approved steel fuel tank design eliminates hydrocarbon emissions.

Premium Square D Circuit Breakers

Square D is the industry leader in circuit breaker protection.

100% Load Tested

Every generator is fully tested prior to leaving our facility.

HOME POWER®

6,000 Surge Watts **5.500 Continuous Watts**



Optional Accessories

Two Wheel. Flat-Free Dollv Kit

Portability is important to get your generator where it needs to be.

Generator Cover

When your generator is not in use, a cover will keep it dust and debris free.

Plug-In Line Voltage Monitor

For when you want to verify the voltage output.

WINCO Emergency Transfer Service Kit

You will be able to set up your generator quickly and safely to restore power to critical circuit breakers.

30 Amp (NEMA L14-30P) Plua

You supply the length of cord you need. We offer the plug.

Low Pressure Fuel Solenoid


For peace of mind when you have to run your generator unattended.

Maintenance Kit

Keep the engine at its peek performance to ensure the generator will be ready when needed most.

Batterv

Interstate group 20 300 CCA.



NEMA L14-30 30A

SPECIFICATIONS

GENERATOR

SURGE WATTS ⁽¹⁾	6,000
CONTINUOUS WATTS ⁽¹⁾	5,500
CONTINUOUS AMPS ⁽¹⁾	45.8/22.9
OUTPUT	120/240 V
VOLTAGE REGULATION	CAPACITOR +/-5%
FREQUENCY REGULATION	+/-3%
MAIN CIRCUIT BREAKER	25 AMP
BONDED NEUTRAL	YES
120 VOLT RECEPTACLES	(1) NEMA 5-20 20A DUPLEX
120/240 VOLT RECEPTACLES	(1) NEMA L14-30 30A
LIFTING EYE	NO
2-WHEEL DOLLY KIT	OPTIONAL
PROTECTIVE ROLL FRAME	14 GAUGE STEEL
GENERATOR WARRANTY ⁽²⁾	2 YRS RESIDENTIAL

NOTES: (1) Based on gasoline fuel. Derate 20% for Natural Gas. (2) For complete generator warranty information, refer to the HPS6000HE manual

SHIPPING

DIMENSIONS (LxWxH)	32.75" x 22.5" x 22"
NET WEIGHT	202 LBS
SHIPPING DIMENSIONS	33" x 25" x 26"
SHIP WEIGHT	224 LBS
FREIGHT CLASS	70



32.75"





ENGINE

ENGINE BRAND	HONDA	
ENGINE MODEL	GX340	
ENGINE STARTER	RECOIL/ELECTRIC	
ENGINE SPEED	3600 RPM	
ENGINE CYLINDERS	SINGLE	
DISPLACEMENT/TYPE	389 CC / OHV	
LOW OIL PROTECTION	STANDARD	
RECOMMENDED OIL	10W-30	
OIL CAPACITY	1.2 QTS	
dBAAT 7 METERS	72	
MOTOR STARTING (CODE G) ⁽¹⁾	2 HP	
BATTERY SIZE ⁽²⁾	BCI 20 OR 24HL 300 CCA	
EPAAPPROVED	YES	
CARB APPROVED	NO	
CSAAPPROVED	NO	
UL LISTED	NO	
ENGINE WARRANTY ⁽³⁾	3 YRS RESIDENTIAL	
NOTES: (1) Code G capacitor start motor. (2) Battery not included (3) Contact your		

NOTES: (1) Code G capacitor start motor. (2) Battery not included (3) Contact your local Honda service center for engine warranty assistance.

FUEL

FUEL TANK		7 GAL
FUEL GAUG	E	ON TANK
FUEL USE:	GASOLINE NATURAL GAS	1 GAL/HR 160 FT ³ /HR - 163,200 BTU/HR



22.5"

GeneratorJoe[®]

4723 Muirfield Court Santa Rosa, CA 95405 Phone: 707 542-2224 Fax: 707 542-2227 Email: sales@generatorjoe.Net Web: www.generatorjoe.NET